

DICOM Correction Proposal

Status	Final Text
Date of Last Update	2016/01/19
Person Assigned	Ulrich Busch (ulrich.busch@varian.com)
Submitter Name	Ulrich Busch (ulrich.busch@varian.com)
Submission Date	2015/06/01

Correction Number	CP-1512
Log Summary: Correction of Motion Mode Attribute Reference	
Name of Standard PS3.3 2015c	
Rationale for Correction: CP-1430 introduced 10.24 Device Motion Control Macro. One attribute reference in the Standard publication needs correction.	
Correction Wording:	

In Part 3, correct the following Macro in section 10:

10.24 Device Motion Control Macro

Table 10-28 specifies the attributes that describe requirements on performing the movement of a device from an actual to a desired position.

Table 10-28
DEVICE MOTION CONTROL MACRO ATTRIBUTES DESCRIPTION

Attribute Name	Tag	Type	Attribute Description
Device Motion Control Sequence	(300A,0450)	3	Device Motion Control Definitions for each degree of freedom. One or more Items are permitted in this sequence.
>Device Motion Parameter Code Sequence	(300A,0453)	1	The parameter for which the Device Motion Control shall be applied.
<i>>>Include 'Code Sequence Macro' Table 8.8-1</i>			<i>Defined CID 9401</i>
>Device Motion Execution Mode	(300A,0451)	1C	Permitted Motion Execution Mode for movement. Required if Device Motion Observation Mode (300A,0452) is absent. May be present otherwise. See 10.24.1.1.

>Device Motion Observation Mode	(300A,0452)	1C	Required Motion Observation Mode for movement. Required if Device Motion Observation Mode (300A,0452) <u>Device Motion Execution Mode (300A,0451)</u> is absent. May be present otherwise. See 10.24.1.2.
---------------------------------	-------------	----	---