

DICOM Correction Item

Correction Number CP-301	
Log Summary: Correct C-MOVE and C-GET response attributes	
Type of Modification	Name of Standard
Clarification	PS 3.4, PS 3.7
Rationale for Correction Technically, the four attributes Number of Remaining / Successful / Failed / Warning Sub-operations in the C-MOVE and C-GET responses are not part of the Identifier; they are part of the Command. Further, although Part 7 tables claim the Identifier includes the matching attributes, that is not specified in the Part 7 or Part 4 text.	
Sections of documents affected PS 3.4 Sections C.4.2.1 and C.4.3.1	
Correction Wording:	

Modify PS3.4 Section C.4.2.1

C.4.2.1.6 Number of Remaining Sub-Operations

...

~~The Identifier in~~ A C-MOVE response with a status of:

- Pending shall contain the Number of Remaining Sub-operations Attribute
- Canceled may contain the Number of Remaining Sub-operations Attribute
- Warning, Failed, Refused, or Successful shall not contain the Number of Remaining Sub-operations Attribute

C.4.2.1.7 Number of Successful Sub-Operations

...

~~The Identifier in~~ A C-MOVE response with a status of:

- Pending shall contain the Number of Successful Sub-operations Attribute
- Canceled, Warning, Failed, Refused, or Successful may contain the Number of Successful Sub-operations Attribute

C.4.2.1.8 Number of Failed Sub-Operations

...

~~The Identifier in~~ A C-MOVE response with a status of:

- Pending shall contain the Number of Failed Sub-operations Attribute
- Canceled, Warning, Failed, Refused, or Successful may contain the Number of Failed Sub-operations Attribute

C.4.2.1.9 Number of Warning Sub-Operations

- ...
- The Identifier in** A C-MOVE response with a status of:
- Pending shall contain the Number of Warnings Sub-operations Attribute
 - Canceled, Warning, Failed, Refused, or Successful may contain the Number of Warning Sub-operations Attribute

Modify PS3.4 Section C.4.3.1

C.4.3.1.5 Number of Remaining Sub-Operations

- ...
- The Identifier in** A C-GET response with a status of:
- Pending shall contain the Number of Remaining Sub-operations Attribute
 - Canceled may contain the Number of Remaining Sub-operations Attribute
 - Warning, Failed, Refused, or Successful shall not contain the Number of Remaining Sub-operations Attribute.

C.4.3.1.6 Number of Successful Sub-Operations

- ...
- The Identifier in** A C-GET response with a status of:
- Pending shall contain the Number of Successful Sub-operations Attribute
 - Canceled, Warning, Failed, Refused, or Successful may contain the Number of Successful Sub-operations Attribute

C.4.3.1.7 Number of Failed Sub-Operations

- ...
- The Identifier in** A C-GET response with a status of:
- Pending shall contain the Number of Failed Sub-operations Attribute
 - Canceled, Warning, Failed, Refused, or Successful may contain the Number of Failed Sub-operations Attribute

C.4.3.1.8 Number of Warning Sub-Operations

- ...
- The Identifier in** A C-GET response with a status of:
- Pending shall contain the Number of Warning Sub-operations Attribute
 - Canceled, Warning, Failed, Refused, or Successful may contain the Number of Warning Sub-operations Attribute

Modify PS3.7 Section 9.3

**Table 9.3-7
C-GET-RSP MESSAGE FIELDS**

Message Field	Tag	VR	VM	Description of Field
Identifier	(no tag)	□	□	A Data Set which encodes the Identifier that was matched that encodes attributes

				providing status information about the C-GET operation. See Section 9.1.3.1.5.
--	--	--	--	--

Table 9.3-10
C-MOVE-RSP MESSAGE FIELDS

Message Field	Tag	VR	VM	Description of Field
Identifier	(no tag)	□	□	A Data Set which encodes the Identifier that was matched that encodes attributes providing status information about the C-MOVE operation. See Section 9.1.4.1.6.